

# Colorcrete Metal Gemstone.

**Colorcrete Metal Gemstone is the metallic finish paint that adds luminosity, shine and luxury to non-trafficable surfaces. Ideal for sophisticated finishes**



## Properties

- Applicable on any type of support: microcement, concrete, brick, ceramic, plasterboard, gypsum, plaster, glass, paper and metals. plasterboard, plaster, glass, paper and metals.
- Applicable by trowel, brush, brush or spray.
- Ready to use product, do not dilute with water.

## Application

The products are prepared for direct application. Before use, homogenize the contents. It is convenient to choose the appropriate method for each application, by trowel, brush, brush or spray gun.

Apply the glaze and let it dry for 8 hours. Depending on the physical and chemical requirements to which the coating will be subjected, apply two coats of Primacrete Finish, or two coats of Primacrete Finish and then Concrete Finish WT, respecting the drying time between coats.

## Special precautions

In case of contact with eyes, rinse with plenty of water for 15 minutes.

In case of contact with skin wash with soap and water. Do not swallow. In case of ingestion do not induce vomiting and seek medical attention immediately.

It is recommended to comply with the following measures:

- Good ventilation.
- Protective goggles to avoid splashing.
- Rubber gloves.

Empty containers should be disposed of in accordance with current legal regulations.

To prevent the product from drying out or thickening close the lid after each use.

Keep out of reach of children.

## Packaging

It is presented in a 0.5 L container.

## Consumption

Performance will depend on the substrate to be coated and the method of application. In the application by trowel the performance is as follows:

- Platinum - 14,00 m<sup>2</sup>/L
- Diamond - 12,00 m<sup>2</sup>/L
- Carnelian - 23,50 m<sup>2</sup>/L
- Ruby - 23,50 m<sup>2</sup>/L
- Amber - 23,50 m<sup>2</sup>/L

If the surface to be coated is in good conditions, better yields will be obtained and also reduce the material cost and application time.

## Storage conditions

The product should be stored in its original closed container and protected from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from heat sources and direct sunlight. The shelf life is 1 year from the date of manufacture, if stored properly.

## Cleaning of the tools

The tools are washed with soap and water, immediately after use.